

RECURVE STEALTH SHOT INSTALLATION INSTRUCTIONS

RECURVE STEALTH SHOT IS AVAILABLE FOR
THE FORMULA ION-X AND TIBURON.

Step 1: Set up and tune your bow as you normally would, WITHOUT the Stealth Shots installed.

Step 2: After your bow is set up and tuned WITHOUT the Stealth Shots installed, measure and make note of your brace height.

Step 3: Take twists out of your string to decrease your brace height by 1/8 of an inch. Make note of how many twists you removed.

Step 4: Install the Stealth Shots on your bow, being mindful to put the top Stealth Shot on the top and the bottom Stealth Shot on the bottom, as they are not interchangeable (See FIG. 1). Use the tapered washers to level the Stealth Shot to the bow riser, using the thicker washer for the top mount and the thinner washer for the bottom (use thick washers for top and bottom on Tiburon bows). The flat part of the washer goes against the Stealthshot and the tapered edge goes against the bow riser. (FIG. 2).

Step 5: After the Stealth Shots are installed, use the set screw (FIG. 3) to adjust the dampers so that they are lightly touching the bow string. It is important that they are not applying any pressure to the string. See (FIG. 4) for recommended orientation of the Stealth Shot dampers, both on top and bottom.

Step 6: Add the twists back to your string that you removed in step 3 to reset your brace height to your original tune. This should leave a gap between the Stealth Shot and the bow string (FIG. 5), which is required for optimal performance and to abide by the rules of World Archery for competition. To be in conformance with World Archery competition rules, the Stealth Shots CANNOT touch the string at brace height.

